



Master-Tube PA 12w

PA tubing containing plasticisers, for industrial and pneumatic applications, temperature- and UV-resistant, abrasion-resistant, impact-resistant

spiral-free

metal-free

Product Details

Construction / Material

- Type of construction: axially extruded tubing without seams or welds
- Execution of the wall: made of highly abrasion-resistant material

Properties

- Specifications of the product: manufactured with calibrated outer diameter
- Chemical Properties: good resistance to chemicals, good UV resistance, halogen-free, hydrolysis resistant, free from paint wetting impairment substances (LABS)
- Mechanical Properties: high resistance to stress corrosion cracking, high mechanical strength and impact resistance

Operating Temperature

- Temperature Range: -40to 90°C

Delivery Information

- Delivery, type of production: inner diameter: 2.0 - 18.0 mm, outer diameter: 4.0 - 22.0 mm

Application Areas

- Areas of application: Wood

Customizing Options

- optional item modification (on request): other colours, multiple hose, spiral version, shaped hose, rolls, cut-to-size sections

Article Variants

Nominal Size (DN) in mm	Inner diameter in mm	Outer diameter in mm	Bending radius* in mm	Weigth in g/m	Operating pressure in bar	Stock Lengths in m	Wall thickness in mm	Tolerance inner & outer diameter in mm
2	2	4	10	9.8	46	/	1	± 0.05
2,9	2,9	4	20	6.2	22	/	0,55	± 0.05
3	3	5	20*	13.1	35*	/	1	± 0.05
4	4	6	20	16.3	29	/	1	± 0.10
5	5	8	30	31.9	35	/	1,5	± 0.10
5,5	5,5	8	40*	27.6	25*	/	1,25	± 0.10
6	6	8	40	22.9	21	/	1	± 0.10
6	6	10	70*	29.4	35*	/	2	± 0.10
7	7	10	40	41.7	25	/	1,5	± 0.10
7,5	7,5	10	70*	35.7	20*	/	1,25	± 0.10
8	8	10	40	29.4	15	/	1	± 0.10
8	8	12	40	65.3	32	/	2	± 0.10
9	9	12	70	51.5	22	/	1,5	± 0.10
10	10	12	90	35.9	13	/	1	± 0.10
10	10	14	120*	78.4	25	/	2	± 0.10
11	11	14	120*	61.3	16*	/	1,5	± 0.10
12	12	15	140*	66.2	15*	/	1,5	± 0.10
12	12	16	140*	91.5	20*	/	2	± 0.15
14	14	18	170*	104.6	17*	/	2	± 0.15
16	16	20	170*	117.6	15*	/	2	± 0.15
18	18	22	200*	130.7	14*	/	2	± 0.25

All data refer to a medium and ambient temperature of 23°C
* Smallest bending radius, related to the inside of the hose bend.
Operating pressure is given with a 3-fold safety factor and applies to the medium air, calculated values are marked with *.

Delivery Variants

Available in other lengths, other nominal diameters, with customer-specific customer-specific imprint.

Disposal instructions

After use, the product must be disposed of in accordance with the legal regulations applicable in the user's region (in Germany in accordance with the applicable Waste Catalogue Ordinance (AVV)).



Individual consultation

We offer consultation by phone: **+49 209 97077 0**

Product requests via: **https://www.masterflex-slang.nl/**

Headquarters for your sales area

Masterflex SE

Willy-Brandt-Allee 300
45891 Gelsenkirchen
Germany