


# Combiflex Dairy Fitting Ring Seal

Sealing ring for solid, liquid and gaseous media in the food industry, pharmaceuticals and chemicals, for threaded spigots to DIN 11851

## Product Details

### Construction / Material

- Specification of the connection solution: for threaded spigots with external milk pipe thread to DIN 11851 from DS 32 - DS 150
- Design of the sealing ring: made of rubber
- Material of the sealing ring: NBR, material complies with the food regulations of DIN 32676 Series A

### Properties

- Chemical Properties: odourless and tasteless, good resistance to chemicals
- Mechanical Properties: excellent mechanical tensile strength and tear resistance
- Colour: blue
- Other: can be sterilised with superheated steam

### Operating Temperature

- Temperature Range: -25to 120°C
- short-term maximum temperature: peaks to 150 °C

## Article Variants

| Article number | DN of the hose in mm | Connection Metric in mm | Inner diameter in mm | Cord thickness |
|---|---|---|---|---|
| 002461 | 32 | 32 | 36 | 5 |
| 002464 | 40 | 40 | 42 | 5 |
| 002467 | 50 | 50 | 54 | 5 |
| 002471 | 65 | 65 | 71 | 5 |
| 002475 | 80 | 80 | 85 | 5 |
| 002479 | 100 | 100 | 104 | 6 |
| 002482 | 125 | 125 | 130 | 7 |

| Article number | DN of the hose in mm | Connection Metric in mm | Inner diameter in mm | Cord thickness |
|---|---|---|---|---|
| 002484 | 150 | 150 | 155 | 7 |

Subject to technical changes and colour deviations

## Delivery Variants

Available in other lengths, other nominal diameters, with customer-specific customer-specific imprint.

## Disposal instructions

After use, the product must be disposed of in accordance with the legal regulations applicable in the user's region (in Germany in accordance with the applicable Waste Catalogue Ordinance (AVV)).



## Individual consultation

We offer consultation by phone: **+49 209 97077 0**

Product requests via: **https://www.masterflex-slang.nl/**

## Headquarters for your sales area

**Masterflex SE**

Willy-Brandt-Allee 300
45891 Gelsenkirchen
Germany