




Combiflex Metal Threaded Sockets

Cast-on threaded connection with external thread according to DIN ISO 228

Product Details

Construction / Material

- Specification of the connection solution: connection thread is designed according to DIN ISO 228, streamlined, liquid-tight connection
- Execution of the sprue / collar: made of highly abrasion-resistant material
- Material of the sprue / collar: polyurethane
- Execution of the nozzle: hose threaded connector design, cast with polyurethane, made of metal, external thread according to DIN ISO 228
- Material of the nozzle: Aluminium

Properties

- Chemical Properties: stainless, odourless and tasteless, good resistance to chemicals
- Mechanical Properties: excellent mechanical tensile strength and tear resistance
- Colour: black
- Other: dissipation of electrostatic charge by grounding connection between hose and fitting

Operating Temperature

- Temperature Range: -40to 90°C
- short-term maximum temperature: peaks to 125 °C

Delivery Information

- Delivery, type of production: various nominal diameters are available ex production, individual nominal diameters also ex stock

Article Variants

Article number	DN of the hose in mm	Piece weight in kg	Connection in Inch	Outer Ø of the sprue on the hose side (d3) in mm
005372	25	0.09	1	42

Article number	DN of the hose in mm	Piece weight in kg	Connection in Inch	Outer Ø of the sprue on the hose side (d3) in mm
005374	32	0.16	1 ¼	52
008448	38	0.21	1 ½	60
/	40	0.21	1 ½	60
005394	50	0.29	2	71
005512	65	0.46	2 ½	90
005417	75	0.78	3	106
/	80	0.60	3 ½	106
005589	100	1.12	4	130
/	125	1.39	5	155
/	150	1.74	6	184

Subject to technical changes and colour deviations

Delivery Variants

Available in other lengths, other nominal diameters, with customer-specific customer-specific imprint.

Disposal instructions

After use, the product must be disposed of in accordance with the legal regulations applicable in the user's region (in Germany in accordance with the applicable Waste Catalogue Ordinance (AVV)).



Individual consultation

We offer consultation by phone: **+49 209 97077 0**

Product requests via: **https://www.masterflex-slang.nl/**

Headquarters for your sales area

Masterflex SE

Willy-Brandt-Allee 300
45891 Gelsenkirchen
Germany