



Metal Cone Flange

metal cone flange based on DIN 3016

Product Details

Construction / Material

- Specification of the connection solution: connection possibility to pipes and pipelines according to DIN 2448 or DIN 2458, streamlined, liquid-tight connection, conical flange coupling system suitable for spigots according to DIN 3016
- Design of the flange: made of steel, steel St 37

Properties

- Chemical Properties: rust-protected
- Other: easy to install due to the use of quick-release clamps, versatile use in connection with steel pieces such as: Bends, reducers and branches

Delivery Information

- Delivery, type of production: various nominal diameters are available ex production, individual nominal diameters also ex stock, individual nominal diameters also ex stock

Customizing Options

- optional item modification (on request): on request available in stainless steel and as screwed part with internal or external thread

Article Variants

Article number	DN of the hose in mm	suitable for / as	Piece weight in kg	Inner Ø of flange or socket (d1) in mm	Outer Ø of the flange (d3) in mm	Outer Ø of the pipe (d2) in mm	Length of the Threaded Socket in mm
002360	50	male part	0.12	54.5	78	60.30	9.5
002359	50	female part	0.12	54.5	78	60.30	9.5
002364	65	male part	0.19	70.3	91	76.10	11.9
002363	65	female part	0.19	70.3	91	76.10	11.9
002371	80	male part	0.23	82.5	104	88.90	11.9

Article number	DN of the hose in mm	suitable for / as	Piece weight in kg	Inner Ø of flange or socket (d1) in mm	Outer Ø of the flange (d3) in mm	Outer Ø of the pipe (d2) in mm	Length of the Threaded Socket in mm
002370	80	female part	0.23	82.5	104	88.90	11.9
002376	100	male part	0.31	107.1	129	114.30	11.9
002375	100	female part	0.31	107.1	129	114.30	11.9
002381	125	male part	0.71	131.7	161	139.70	13.4
002380	125	female part	0.71	131.7	161	139.70	13.4
002388	150	male part	0.90	159.3	190	168.30	13.4
002387	150	female part	0.90	159.3	190	168.30	13.4
002393	160	male part	1.04	167.8	200	177.80	13.4
002392	160	female part	1.04	167.8	200	177.80	13.4
002399	180	male part	1.17	182.9	216	193.70	13.4
002398	180	female part	1.17	182.9	216	193.70	13.4
002403	200	male part	1.40	207.3	242	219.10	13.4
002402	200	female part	1.40	207.3	242	219.10	13.4
002407	250	male part	1.75	260.4	295	273.00	13.4
002406	250	female part	1.75	260.4	295	273.00	13.4

Subject to technical changes and colour deviations

Delivery Variants

Available in other lengths, other nominal diameters, with customer-specific customer-specific imprint.

Disposal instructions

After use, the product must be disposed of in accordance with the legal regulations applicable in the user's region (in Germany in accordance with the applicable Waste Catalogue Ordinance (AVV)).



Individual consultation

We offer consultation by phone: **+49 209 97077 0**

Product requests via: **https://www.masterflex-slang.nl/**

Headquarters for your sales area

Masterflex SE

Willy-Brandt-Allee 300
45891 Gelsenkirchen
Germany