


Combiflex PU Hose Connector

screw-on PU hose connector for Master-PUR L and H hoses

Product Details

Construction / Material

- Specification of the connection solution: tension-resistant and largely leak-proof connection
- Design of the hose connector: high mechanical strength and impact resistance, made of abrasion resistant material
- Material of the hose connector: polyurethane

Properties

- Chemical Properties: hydrolysis resistant, microbe-resistant
- Colour: black
- Other: reusable and replaceable, easy to assemble

Operating Temperature

- Temperature Range: -40to 90°C
- short-term maximum temperature: peaks to 125 °C

Delivery Information

- Delivery, type of production: various nominal diameters are available ex production, individual nominal diameters also ex stock

Article Variants

Article number	DN of the hose in mm	Piece weight in kg	Length (h1) in mm
002020	25	0.09	65
002021	32	0.10	70
002022	38	0.13	75
002023	50	0.20	90
002025	65	0.23	100

Article number	DN of the hose in mm	Piece weight in kg	Length (h1) in mm
002028	80	0.39	115
002029	100	0.58	125

Subject to technical changes and colour deviations

Delivery Variants

Available in other lengths, other nominal diameters, with customer-specific customer-specific imprint.

Disposal instructions

After use, the product must be disposed of in accordance with the legal regulations applicable in the user's region (in Germany in accordance with the applicable Waste Catalogue Ordinance (AVV)).



Individual consultation

We offer consultation by phone: **+49 209 97077 0**

Product requests via: **https://www.masterflex-slang.nl/**

Headquarters for your sales area

Masterflex SE

Willy-Brandt-Allee 300
45891 Gelsenkirchen
Germany